

MODEL NUMBER	PT232161	
RATED INPUT	1 mA	2 mA
RATED OUTPUT	1 mA	2 mA
OPTIMAL LOAD	$\leq 200\Omega$	$\leq 200\Omega$
ACCURACY GRADE	0.1 / 0.2 (RATIO ERROR ONLY)	
DIMENSIONS	<p>The technical drawing shows two views of the PT232161 sensor. The front view (left) shows a rectangular component with a width of 19.5 and a height of 18.2. It has two mounting tabs at the bottom, each 4.0 high and 0.8 wide. The top view (right) shows a square component with a side length of 19.5. It features two internal coils, each connected to two terminals labeled 1, 2, 3, and 4. The distance between the terminals of each coil is 14.0. The distance between the terminals of the two coils is 12.8. The overall height of the top view is 18.0. Asterisks (*) are placed near terminals 2 and 4.</p>	

MODEL NUMBER	PT232361	
RATED INPUT	1 mA	2 mA
RATED OUTPUT	1 mA	2 mA
OPTIMAL LOAD	$\leq 200 \Omega$	$\leq 500 \Omega$
ACCURACY GRADE	0.1 / 0.2 (RATIO ERROR ONLY)	
DIMENSIONS		

MODEL NUMBER	PT232461	
RATED INPUT	1 mA	2 mA
RATED OUTPUT	1 mA	2 mA
OPTIMAL LOAD	$\leq 200 \Omega$	$\leq 200 \Omega$
ACCURACY GRADE	0.1 / 0.2 (RATIO ERROR ONLY)	
DIMENSIONS	<p>The technical drawing shows two views of the sensor. The front view (left) is a square with a width of 19.0 and a height of 18.2. It has two mounting holes, each with a diameter of 5.0 and a distance of 0.8 from the bottom edge. The side view (right) shows a thickness of 10.0 and a distance of 7.2 from the bottom edge to the top of the sensor body. The top view shows a width of 16.2 between the two terminals. The terminals are labeled 1, 2, 3, and 4. Terminals 1 and 2 are on the left, and 3 and 4 are on the right. Terminals 2 and 3 are marked with an asterisk (*). Red coils are shown on terminals 1-2 and 3-4.</p>	

MODEL NUMBER	PT232561	
RATED INPUT	1 mA	2 mA
RATED OUTPUT	1 mA	2 mA
OPTIMAL LOAD	$\leq 200 \Omega$	$\leq 200 \Omega$
ACCURACY GRADE	0.1 / 0.2 (RATIO ERROR ONLY)	
DIMENSIONS		